

© WPI / DERWENT

AN - 2003-158078 [16]
 TI - Preparing ~~aluminum-titanium~~ alloy by direct electrolysis with ~~carbon anode containing titanium oxide~~
 AB - CN1376813 NOVELTY - Preparing an Al-Ti alloy by direct electrolysis of a carbon anode containing ~~titanium~~ oxide includes mixing calcined petroleum coke (73-81 wt.%), coal asphalt (17-25) and ~~titanium~~ oxide powder (0.5-5), heating while kneading for 30-45 minutes, shaping the anode, calcining, installing the anode into an electrolyzer and electrolyzing. Its advantages are high performance of product, low cost, high uniformity and high current efficiency.
 - (Dwg.0/0)
 IW - PREPARATION ALUMINIUM TITANIUM ALLOY DIRECT ELECTROLYTIC CARBON ANODE CONTAIN ~~TITANIUM~~ OXIDE
 PN - CN1376813 A 20021030 DW200316 C25C3/36 000pp
 IC - C25C3/36
 MC - M26-B06 M26-B06A M26-B09 M26-B09T M28-B M28-C01
 - X25-R02
 DC - M26 M28 X25
 PA - (ZHEN-N) ZHENGZHOU INST LIGHT METALS
 IN - GU S; LIU F
 AP - CN20010138370 20011228
 PR - CN20010138370 20011228

XP002325420.

BEST AVAILABLE COPY